

3006102041

EHS-240

Rotary Light 24V DC, Orange





Description

- ✓ Used in noisy areas to indicate a call
- ✓ Equipped with 1m Cable
- ✓ 24 VDC

Rotating beacon in painted mild steel housing, for less aggressive environments. Enduring with low noise friction-gear.

Technical Dimensions



Specifications

GENERAL

Operating voltage	24V DC +-10%
Lamp source	70 W halogen (H1)
Rated current	3A
Flash frequency	180 r.p.m.
Operating temp	-10°C to +50°C
Material	Housing : Painted mild st. / Lens : PC
Housing Colour	Grey
Duty cycle	100%
Connection	1mtr. cable
IP-class	IP-54
Dimensions (mm)	148Ø x 215H
Weight	1.1 kg

ORDER NUMBER

DESCRIPTION

3006102038	EHS-24B Rotary Light 24VDC Blue
3006102039	EHS-24G Rotary Light 24VDC Green
3006102040	EHS-24K Rotary Light 24VDC Clear
3006102041	EHS-24R Rotary Light 24VDC Orange
3006102042	EHS-24R Rotary Light 24VDC Red

ACCESSORIES

3006102051	Spare Lens for EHS, Blue
3006102052	Spare Lens for EHS, Orange
3006102053	Spare Lens for EHS, Green
3006204181	Spare Lens for EHS, Clear
3006102082	Spare Lens for EHS, Red